

Manufacturing Commercial Bricks with Illinois Coal Fly Ash

A Program Overview

Mei-In (Melissa) Chou^{1,2} and Francois Botha³

Illinois State Geological Survey¹,
University of Illinois at Urbana-Champaign, Dept. of Natural Resources and
Environmental Science²
and Illinois Clean Coal Institute³

2003 International Coal Ash Utilization Symposium
October 20-24, 2003, Lexington, Kentucky

Outline

- Background Information
- Research and Development
 - Laboratory-scale tests
 - Pilot plant tests
- Commercial Production
 - Commercial-scale tests
- Summary
- Recommendations
- Acknowledgments

Background Information

- Three million tons of Class F fly ash generated each year in Illinois
- Majority of this coal combustion by-product is ponded or landfilled
- No high-volume commercial uses in cement-related construction products


Chemical Composition Comparison

Chemical composition of Class F ash is similar to the raw materials of a conventional fired brick

wt%	Clay	Shale	FA-1	FA-2
SiO ₂	57.10	63.30	53.47	48.96
Al ₂ O ₃	25.04	16.65	21.10	22.47
Fe ₂ O ₃	2.33	6.54	10.82	13.34
SiO₂+Al₂O₃+Fe₂O₃	84.47	86.49	85.39	84.47
CaO	0.46	0.39	3.28	1.35
MgO	0.53	1.79	1.09	0.83
Na ₂ O	0.02	0.92	1.58	1.50
K ₂ O	1.42	3.14	2.67	2.36
S	0.8	0.2	0.4	0.5
Loss On Ignition	8.84	4.49	2.77	6.64

FA-1 =Illinois Class F, Fly ash-1; FA-2 =Illinois Class F, Fly ash-2

Traditional Fired Brick Manufacturing



Brick Industry Association

Research and Development

ISGS/UIUC Research Project (1999-2001)


Laboratory-scale tests

- Conducted laboratory-scale tests
- Used various Illinois fly ashes
- Produced bricks with inputs of fly ash up to 70 wt%
- Performed characterization
- Performed market and preliminary economic analyses

Pilot plant tests


- Performed 300-brick pilot plant tests
- Established bench unit tests - resolved various issues
- Produced bricks from pilot plant test with 40 wt% fly ash

Compressive strength of fired laboratory-size test bricks



Thermal conductivity (at 32⁰F) of fired laboratory-size test bricks

with and without 50 wt% fly ash



Pilot Plant Tests

Issues

Extrusion

- Low plasticity
- High plasticity

Firing


- Scumming
- Lime pops
- Black cores
- Bloating

Pilot Plant Tests



Successful firing of green bricks, containing 40 wt % fly ash,
produced from a pilot plant test run

Pilot Plant Tests



Test wall built using fired bricks from pilot plant production

Commercial Production

ISGS/UIUC Commercial Production Project (2002-2003)

Using a beehive kiln

- Performed 5,000-brick production test
- Performed 10,000-brick production tests

Using a tunnel kiln

- Performed 2,800-brick production tests

Continued market and economic analyses

Commercial-Scale Tests



Commercial-scale extrusion test run producing three-hole green bricks

Commercial-Scale Tests



Regular commercial
bricks with no fly
ash

Three-hole building bricks with 40 vol% fly ash
- 5,000 bricks per batch fired in a beehive kiln

Commercial-Scale Tests



Ten-hole building bricks with 20 wt% fly ash
- 1,400 bricks per batch fired in a tunnel kiln

Commercial-Scale Tests

Compressive strength and water absorption properties of commercial-size test bricks made with ponded Illinois coal fly ash, Fly ash-2

			Pilot plant 3-hole-brick production test	Commercial-scale 3-hole-brick production test
Engineering properties		ASTM C 62 Standard Specification	Fly ash-2 : GCM mix 40 wt% : 60 wt%	Fly ash-2 : CBC shale : CBC clay 40 vol% : 40 vol% : 20 vol%
Max. water absorption	Cold water 24 hr (%)	# 8	6.20	6.50
	Boiling water 5 hr (%)	# 17	8.50	9.10
	Saturation coefficient	# 0.78	0.73	0.71
Fired compressive strength (psi)		3,000	12,930	15,770
ASTM grade		SW	SW	SW

GCM mix = Global Clay Marseilles' Mix at 60 wt% shale and 40 wt% clay; CBC = Colonial Brick Company; and SW= severe weather application

Potential Production Cost Saving Estimation: A Case Study

Based on the current mining and processing costs for the conventional raw materials, the cost of obtaining fly ash from a nearby available source, and the production cost of manufacturing fired bricks with 40 wt% fly ash:

- *Case I*, producing 12 million bricks per year and obtaining fly ash at \$3.25/ton, could realize an annual production cost savings of \$47,650
- *Case II*, producing 27 million bricks per year and obtaining fly ash at \$5/ton, could realize an annual production cost savings of \$12,891

Summary

Process

- Uses conventional equipment
- Is potentially more energy efficient and less expensive

Product

- Produced with 20 wt% to 40 wt% fly ash from two Illinois sources
- Properties met or exceeded commercial specifications

Optimization

- Relies on the source and properties of the fly ash and the operation parameters of a specific brick plant

Recommendations and Further Work

- Since quality of the bricks produced with fly ash relies on the source and properties of the fly ash and the operation parameters of a specific brick plant, feasibility evaluation should be conducted on a case-by-case basis.
- ISGS/UIUC-developed fly ash brick process is nearly ready for commercialization at some brick plants. The ISGS/UIUC will continuously make its facility and expertise available to assist in advancing the fly ash brick-making process to commercial status.



An Illinois coal fly ash brick wall on display
at the Chicago Museum of Science and Industry

Acknowledgments

- This project was supported in part by grants from the Illinois Department of Commerce and Economic Opportunity, through the Office of Coal Development and the Illinois Clean Coal Institute.
- Authors thank S.-F. J. Chou (ISGS), V. Patel (ISGS), and J. W. Stucki (UIUC) for their contributions as co-investigators. Thanks also go to the industrial participants, including Global Clay Marseilles, J.C. Steel & Son, Colonial Brick Company, Richards Brick Company, Streator Brick Company, Ameren CIPS, Dynegy Midwest Generation, Inc. for their technical discussions and for providing test facilities, including fly ash, clay, and shale raw materials.

Disclaimer Statement

This publication was prepared by the Illinois State Geologic Survey. Neither the Illinois State Geologic Survey, any of its subcontractors, the Illinois Department of Commerce and Economic Opportunity, Illinois Clean Coal Institute, nor any person acting on behalf of either

A. makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. assumes any liabilities with respect to the use of, or damages resulting from the use of, any information, apparatus, method, or process disclosed in this project.

Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring; nor do the views and opinions of authors expressed herein necessarily state or reflect those of the Illinois Department of Commerce and Economic Opportunity, the Office of Coal Development, or the Illinois Clean Coal Institute.

Notice to Publishers: If you borrow information from any part of this project, you must include a statement about the State of Illinois' support of the project.